

YIHUA TRAILER Series

Diesel Generator Sets



CE EPA ISO9001

Technical Data

Model	Rated Power (KW)	Rated Volt. (V)	Rated Current (A)	Fre. (Hz)	Generator model	Wheels No.
GT-10	10	400/230	18.1	50/60	TFW2-10	TWO
GT-12	12	400/230	21.6	50/60	TFW2-12	TWO
GT-15	15	400/230	27.2	50/60	TFW2-15	TWO
GT-20	20	400/230	36.1	50/60	TFW2-20	TWO
GT-24	24	400/230	43.3	50/60	TFW2-24	TWO
GT-30	30	400/230	54.1	50/60	TFW2-30	TWO
GT-40	40	400/230	72.1	50/60	TFW2-40	TWO
GT-50	50	400/230	90.2	50/60	TFW2-50	TWO
GT-64	64	400/230	115.8	50/60	TFW2-64	FOUR
GT-75	75	400/230	135.3	50/60	TFW2-75	FOUR
GT-90	90	400/230	162.3	50/60	TFW2-90	FOUR
GT-100	100	400/230	180.4	50/60	TFW2-100	FOUR
GT-120	120	400/230	216.5	50/60	TFW2-120	FOUR
GT-150	150	400/230	271	50/60	TFW2-150	FOUR
GT-200	200	400/230	361	50/60	TFW2-200	FOUR
GT-250	250	400/230	451	50/60	TFW2-250	FOUR
GT-300	300	400/230	541	50/60	TFW2-300	FOUR
GT-320	320	400/230	579.2	50/60	TFW2-320	FOUR
GT-350	350	400/230	633.5	50/60	TFW2-350	FOUR

Special Voltage also available

Note: All the parameter is provided for the convenience of our customers as accurately as possible. YIHUA reserves the right to modify the data at any time